ATTESTATION OF CONFORMITY

Issued to: HDL Automation Co., Ltd.

No.86 Lotus west Road. Lifeng Street, Shilou Town, Panyu District, Guangzhou

511447 China

For the product: Battery Unit

xenterra

Trade name:

Type/Model: ME-GSE-B5K, ME-GSE-B10K, ME-GSE-B15K, ME-GSE-BMS15K

Ratings: See annex

Manufactured by: HDL Automation Co., Ltd.

No.86 Lotus west Road. Lifeng Street, Shilou Town, Panyu District, Guangzhou

511447 China

Subject: Complete evaluation of electrical system of the appliances

Requirements: EN IEC 61000-6-3;2021

EN IEC 61000-6-1:2019

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a test file / test report no 4910456.50.

This Attestation implies that the examined types are in accordance with the standards designated under the Electromagnetic Compatibility Directive (EMC) 2014/30/EU.

The examination has been carried out on one single specimen of several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of this production with the specimen tested by DEKRA is not the responsibility of DEKRA.

This document does not authorize the use of any DEKRA approved mark.

Arnhem, 11 November 2024 Number: 4910456.01AOC

DEKRA Testing and Certification (Shanghai) Ltd., Guangzhou Branch

Miranda Zhou Certification Manager

 $\ensuremath{\mathbb{C}}$ Integral publication of this attestation and adjoining reports is allowed

DEKRA Testing and Certification (Shanghai) Ltd., Guangzhou Branch Block 5, No.3, Qiyun Road, Huangpu District, Guangzhou, Guangdong, China T +86 20 6661 2000 F +86 20 6661 2001 www.dekra-product-safety.com



Annex

Document no. : 4910456.01AOC

Ratings:

atings:		
	Model name	Ratings
BMS	ME-GSE-BMS15K	For Charge mode:
		Input Voltage Range: 450 – 1100VDC,
		Max. Input Current: 20A
		Output Voltage Range: 230 -876VDC,
		Max. Output Current: 10A
		For Discharge mode:
		Input Voltage Range: 230 – 876VDC,
		Max. Input Current: 10A
		Output Voltage Range: 450 -900VDC,
		Max. Output Current: 20A
Battery pack	ME-GSE-B5K,	Operation voltage range: 224 – 280VDC,
		Maximum discharge current: 20A,
		Maximum discharge power: 5.12kW,
		Maximum charge current: 10A,
		Maximum charge power: 2.5 kW
	ME-GSE-B10K,	Operation voltage range: 448 – 560VDC,
		Maximum discharge current: 20A,
		Maximum discharge power: 10.24 kW,
		Maximum charge current: 10A,
		Maximum charge power: 5 kW
	ME-GSE-B15K	Operation voltage range: 672 – 840VDC,
		Maximum discharge current: 20A,
		Maximum discharge power: 15 kW,
		Maximum charge current: 10A,
		Maximum charge power: 7.5 kW